



## MORTELAN Cemento blanco

- Bathroom and kitchen repairs.
- Tile, bathroom fitting and plumbing fixing.
- Join finishing between walls and floors.

### Description and uses of the product

Prepared hydraulic binder of excellent whiteness and high strength, ready to mix with aggregates of different granulometry and nature (limestone, siliceous, dolomite, etc.), and perform different types of masonry mortar (masonry works, masonry in general, plasters, etc.).

Its applications are extended to:

- Repairs in bathrooms and kitchens.
- Realization of grouts in pavements and ceramic coatings, stone material and swimming pools.
- Fixation of toilets and plumbing.
- Placement of platelets, tiles and terraces.
- Completion in joints between walls and floors.
- Floors and base for pavements.
- Repairs on concrete, stone or brick.

It can be used interchangeably indoors and outdoors.

### How to use

- 1) Prepare and clean substrate.
- 2) Water to add 0.500 litres / 1.5 kg bag
- 3) Manual application.
- 4) Setting time 3 hours.
- 5) Clean tools with water.

### Recommendations:

Application temperature + 5°C to + 30°C

Wet the supports before applying the product.

To improve bonding on old concrete, it is recommended that 1 litre of **GECOL LÁTEX** be added to the mixture for every 5 – 10 kg of mixture.

Apply with a float or palette knife.

Do not use on gypsum or plaster surfaces.

### Features

Colour: White.

Mix life: Approx. 3 h.

Compression resistance after 28 days: > 42.5 N/mm<sup>2</sup>.

Shelf life 12 months if sheltered.



## MORTELAN Cemento blanco

### Yield

It varies according to the type of application.  
Theoretical consumption 1.2 kg / m<sup>2</sup> per mm of thickness.

### Presentation and delivery

1.5 kg inner polypropylene bag in plastic bucket and pallet with 160 buckets (240 kg).  
4.5 kg (3 x 4.5 kg) inner polypropylene bag in plastic bucket and pallet with 105 buckets (472.5 kg).

### Precautionary statements



#### **Danger**

#### **Hazard statements**

**H315:** Causes skin irritation

**H318:** Causes serious eye damage

**H317:** May cause an allergic skin reaction

**H335:** May cause respiratory irritation

#### **Precautionary statements**

**P261:** Avoid breathing dust/fume/ gas/mist/vapours/spray.

**P280:** Wear protective gloves/protective clothing/eye protection/face protection.

**P302 + P352** – IN CASE OF SKIN CONTACT: Wash with plenty of soap and water.

**P305 + P351 + P338** – IN CASE OF EYES CONTACT: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**P310:** Immediately call a POISON CENTER/doctor

**1999/45/CE** The product contains a chromium VI reducing agent; the period of declared efficiency is that indicated on the packaging.