



## MORTELAN Cemento rápido

- Sealing of water leaks.
- Repairs and joints in drains.
- Emergency work.
- Quick anchors and seals.

### Description and uses of the product

Quick-setting cement, suitable for fixings and flush-mounted installations that require immediate commissioning.

Suitable for any masonry work in which short-term resistance is required, in jobs such as: anchors, frames, rules, pipes, hinges, fixing of street furniture (signs, sewer covers, drains, etc.), in contact with water or in environments with a high degree of humidity.

Valid for sealing waterways in cracks and fissures of concrete or other cement-based surfaces, as well as for filling and repairing concrete pipes and tanks.

It can be mixed with sand in a ratio of 1: 3 volumes to make fast mortars of plaster.

It can be used interchangeably indoors and outdoors.

### How to use

- 1) Prepare and clean substrate.
- 2) Water to add 0.500 litres / bag 1.5 kg.
- 3) Manual application
- 4) Setting time 3-6 minutes.
- 5) Clean tools with water.

### Recommendations:

Application temperature + 5°C to + 30°C

Do not mix the product again once it begins to set. Mix and apply immediately.

Apply with a float or spatula. When used to seal water ways, mix rapidly with water to achieve a thick consistency, either on a plastic sheet or using rubber gloves.

When setting begins, immediately apply the mixture to the point which needs sealing, applying pressure until the product has set.

Avoid using excessive amounts of water.

Do not use on gypsum or plaster surfaces.

### Features

Colour: Grey.

Resistant to weathering and humidity.

Setting time: Approx. 3-6 minutes.

Neither shrinks nor cracks once set.

Waterproof.

It develops high mechanical resistances in a short time (15 minutes).

Shelf life 12 months if sheltered.



## MORTELAN Cemento rápido

### Yield

It varies according to the type of application.  
Theoretical consumption 1.5 kg / m<sup>2</sup> per mm of thickness.

### Presentation and delivery

1.5 kg inner polypropylene bag in plastic bucket and pallet with 160 buckets (240 kg).  
4.5 kg (3 x 4.5 kg) inner polypropylene bag in plastic bucket and pallet with 105 buckets (472.5 kg).

### Precautionary statements



#### **Danger**

#### **Hazard statements**

**H315:** Causes skin irritation

**H318:** Causes serious eye damage

**H317:** May cause an allergic skin reaction

**H335:** May cause respiratory irritation

#### **Precautionary statements**

**P261:** Avoid breathing dust/fume/ gas/mist/vapours/spray.

**P280:** Wear protective gloves/protective clothing/eye protection/face protection.

**P302 + P352** – IN CASE OF SKIN CONTACT: Wash with plenty of soap and water.

**P305 + P351 + P338** – IN CASE OF EYES CONTACT: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**P310:** Immediately call a POISON CENTER/doctor

**1999/45/CE** The product contains a chromium VI reducing agent; the period of declared efficiency is that indicated on the packaging.