



MORTELAN
SOLUCIONES PARA TU CASA



PREPARADO DE
ESCAYOLA

Moulding plaster and repair.

Restoration of mouldings, rose-work, ceiling and false ceilings.

Description and uses of the product

Prepared plaster, fine finishing, easy application and sanding, undiminished, valid for moulding, craftwork and repair plaster decorative materials such as mouldings, panels, rosettes, ceilings, etc., indoors quickly and economic.

It is also suitable for filling cracks and holes in all kinds of supports, as well as small repairs on plasterboard.

How to use

- 1) Prepare and clean substrate.
- 2) Water to add 0,500 litres / sac 1 kg.
- 3) Manual application.
- 4) Mixture workable for 10 minutes.
- 5) Clean tools with water.

Recommendations:

Do not use at low temperatures.

The supports must be bonded well, should this not be the case apply a primer.

Wet the support before applying the product.

Apply the mixture with a float or palette knife when filling holes and with a plastering trowel when laying.

Precautionary statements

P102 Keep out of reach of children.

P260 Do not breathe dust.

P262 Do not get in eyes, on skin, or on clothing.

P280 Wear protective gloves/eye protection/face protection.

Features

Smooth matt white finish.

Setting time: 30 min.

Resistance to flexural strength: 35 kg/cm².

Shelf life 12 months if sheltered.

Yield

It varies depending on the type of application.

Theoretical consumption +/- 1 kg / m² per mm thickness.

Presentation and delivery

1 kg inner polypropylene bag in plastic bucket and pallet with 160 buckets (160 kg).

3 kg (3 x 1 kg) inner polypropylene bag in plastic bucket and pallet with 105 buckets (315 kg).