

ESCAYOLA

FINE
FINISH

Moulding plaster and repair.

Restoration of mouldings, rose-work, ceiling and false ceilings.



Description and uses of the product

Plaster preparation, fine finish, easy application and sanding.

No waste, valid for molding, manual work and repair of decorative plaster materials such as: mouldings, ceilings, rosettes, false ceilings, etc., indoors

It is also suitable for filling cracks and holes in all kinds of supports, as well as small repairs on plasterboard.

"Reparation of decorative materials"

How to use

1. Prepare and clean substrate.
2. Water to add 0,500 litres / sac 1 kg.
3. Manual application.
4. Mixture workable for 10 minutes.
5. Clean tools with water.

Recommendations

Do not apply at temperatures below 5°C.

On highly absorbent or crumbly substrates it is recommended to apply the **GECOL Primer-TP** 1:2 surface consolidator diluted in water.

Wet the support before using the product.

Use a spatula or a trowel depending on the operation to realize.

Do not apply on constantly damp substrates.

Features

Smooth matt white finish.

Setting time: 30 min.

Resistance to flexural strength: 35 kg/cm².

Shelf life 12 months if sheltered.

Yield

It varies depending on the type of application.

Theoretical consumption : 1kg/m² per mm thickness.

Presentation and delivery

1 kg bucket: 1 kg polypropylene bag in plastic buckets for mixing.

3 kg bucket: 3 polypropylene bags of 1 kg (3 x 1 kg) in plastic mixing buckets.

Precautionary statements

P102 Keep out of reach of children.

P260 Do not breathe dust.

P262 Do not get in eyes, on skin, or on clothing.

P280 Wear protective gloves/eye protection/face protection.