

# JUNTA BLANCO POLAR

EASY  
CLEANING

ANTI-MOLD  
EFFECT

Filling ceramic tile, terrazzo and flexible tile joints on floors.

Swimming pool repairs.



## Description and uses of the product

Mortar of deformable cement, monocomponent and impermeable, of excellent whiteness, developed for the filling of fine joints (up to 5 mm) in all types of ceramics, marbles, granites, natural stones, etc.

It can be applied indistinctly in floor and wall coverings, both indoors and outdoors, as well as in humid environments such as bathrooms, kitchens and even swimming pools.

Valid for the realization of joints in partitions and wood (windows, doors, etc.)

*"Up to 5 mm"*

Excellent cleaning, high resistance to abrasion and very fine texture (no scratch), which allows for impeccable finishes.

This board incorporates in its formulation a biocide and fungicide preservation system, thus avoiding the appearance of mold and other microorganisms.

## How to use

1. Prepare and clean substrate.
2. Water to add 0,400 litres / 1,5 kg bag
3. Mixture workable for 1 hour
4. Yield 0,300 - 0,600 kg / m<sup>2</sup>.
5. Clean tools with water.

## Recommendations

Application temperature from 5 °C to 30 °C.

Apply with a rubber spatula diagonally over the joint, pressing without rubbing. When the product begins to harden, clean with a damp sponge and then remove the remains with a dry cloth.

If the surface of the covering is not glazed (porous), carry out a washability test of the mortar before laying. In the case of pigmented mortar, protect the surface with a wax, to prevent pigments from penetrating into the coating.

Do not apply on gypsum or metal substrates.

## Features

Colour: White.

High performance flexible ceramic joints, type CG2 W A

Compression resistance: > 25 N/mm<sup>2</sup>

Mix life: Approx. 1 hours.

## Yield

It varies according to the dimensions of the ceramic, width and depth of the joint. (kg/m<sup>2</sup>)

### Estimated consumption

mm	5 x 5	10 x 10	15 x 15	20 x 20	30 x 30
1	0,3	0,2	0,2	0,2	0,1
2	0,6	0,3	0,4	0,3	0,2
3	0,9	0,4	0,6	0,4	0,3
4	1,0	0,6	0,6	0,5	0,4
5	1,2	0,7	0,7	0,6	0,5

## Presentation and delivery

**1,5 kg bucket:** 1.5 kg polypropylene bag in plastic buckets for mixing.

**4,5 kg bucket:** 3 x 1.5 kg polypropylene bags (3 x 1.5 kg) in plastic mixing buckets.

## Safety data



GHS07

### Hazard statements

- H315** Causes skin irritation.  
**H318** Causes serious eye damage.  
**H317** May cause an allergic skin reaction.  
**H335** May cause respiratory irritation.

### Precautionary statements

- P261** Avoid breathing dust/fume/ gas/mist/vapours/spray.  
**P280** Wear protective gloves/protective clothing

/eye protection /face protection.

**P302 + P352 IN CASE OF SKIN CONTACT:**  
Wash with plenty of soap and water.

**P305 + P351 + P338 IN CASE OF EYES CONTACT:**  
Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do.  
Continue rinsing.

**P310** Immediately call a POISON CENTER/doctor  
**1999/45/CE** The product contains a chromium VI reducing agent; the period of declared efficiency is that indicated on the packaging.