

MORTERO DE ALBAÑILERÍA

HIGH
RESISTANCE

Masonry mortar in general.

Ready to use for plastering and plastering.

All types of brick partition, concrete block and stone.



Description and uses of the product

Dry mortar of cement and siliceous aggregates of first quality, prepared for its use.

Suitable for all types of general masonry works: masonry, plaster, assembly and assembly of cement blocks or ceramic bricks, creation of screeds and screeds, making high strength anchors, etc.

Being a product previously prepared and dosed, avoid mixing cement with sand and possible errors as a result of these. You only need to add the corresponding water.

'All kinds of masonry works'

Of great plasticity, very easy application and workability.

It can be used interchangeably indoors and outdoors.

How to use

1. Prepare and clean substrate.
2. Water to add 0,500 litres / 2 kg bag
3. Manual application.
4. Mixture workable for 90 minutes.
5. Clean tools with water.

Recommendations

Application temperature: from +5 °C to +30 °C.

Apply with a float or trowel.

Do not use on gypsum, paint or degradable product bonds.

Do not mix the product again once it begins to set.

Avoid using excessive amounts of water.

Features

Dry mortar type GM 7,5.

Color grey.

Weather and moisture resistant.

Resistance to compression: > 7,5 N/mm².

Shelf life 12 months if sheltered.

Yield

It varies according to the type of application.

Theoretical consumption: 1,5 kg/m² per mm of thickness.

Presentation and delivery

2 kg bucket: 2 kg polypropylene bag in a plastic mixing bucket.

6 kg bucket: 3 polypropylene bags of 2 kg (3 x 2 kg) in a plastic mixing bucket.

Safety data



GHS07

Hazard statements

- H315** Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

Precautionary statements

- P261** Avoid breathing dust/fume/ gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing

/eye protection /face protection.

P302 + P352 IN CASE OF SKIN CONTACT:
Wash with plenty of soap and water.

P305 + P351 + P338 IN CASE OF EYES CONTACT:
Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do.
Continue rinsing.

P310 Immediately call a POISON CENTER/doctor
1999/45/CE The product contains a chromium VI reducing agent;
the period of declared efficiency is that indicated on the packaging.