

PLASTE INTERIORES

FINE
FINISH

Plastering, smoothing and cover small cracks and damages.

Fine finish, durable and high-quality white.

Fast drying, good adhesion, no shrinkage.



Description and uses of the product

Spackling powder, designed to repair minor damage, plastering, smoothing and cover cracks in coatings and ceilings.

It provides a fine, durable and high-quality finish, and can be applied on plaster, gypsum boards, paints, cement, concrete and other similar nature. It is also recommended use for smoothing and leveling walls after removal of wallpaper.

Thanks to its fine particle size and fast drying, provides a simple and sanding with zero shrinkage.

'Small damage repair'

Reduced and homogenised support absorption, saving paint accordingly.

How to use

1. Prepare and clean substrate.
2. Water to add 0,600 litres / sac 1,5 kg.
3. Manual application.
4. Mixture workable for 6 hours.
5. Clean tools with water.

Recommendations

Do not apply at temperatures below 5 °C.

Do not apply on supports with permanent humidity.

In the case of non-consistent supports, the application of **GECOL Primer-TP** 1:2 surface consolidant diluted in water is recommended.

Protect metal parts with an anticorrosive primer.

Apply with a trowel or trowel depending on the operation to be carried out.

Features

Colour: White.

Drying time: 2 - 4 h. x mm.

Shelf life 12 months if sheltered.

Yield

It varies depending on the type of application.

Theoretical consumption +/- 1 kg / m² per mm thickness.

Presentation and delivery

1,5 kg bucket: 1.5 kg polypropylene bag in a plastic mixing bucket.

4,5 kg bucket: 3 polypropylene bags of 1.5 kg (3 x 1.5 kg) in a plastic mixing bucket.

Precautionary statements

P102 Keep out of reach of children.
P260 Do not breathe dust.

P262 Do not get in eyes, on skin, or on clothing.
P280 Wear protective gloves/eye protection/face protection.