



MORTELAN
SOLUCIONES PARA TU CASA



PLASTE INTERIORES

Plastering, smoothing and cover small cracks and damages.

Fine finish, durable and high-quality white.

Fast drying, good adhesion, no shrinkage.

Description and uses of the product

Spackling powder, designed to repair minor damage, plastering, smoothing and cover cracks in coatings and ceilings.

It provides a fine, durable and high-quality finish, and can be applied on plaster, gypsum boards, paints, cement, concrete and other similar nature. It is also recommended use for smoothing and leveling walls after removal of wallpaper.

Thanks to its fine particle size and fast drying, provides a simple and sanding with zero shrinkage.

Reduced and homogenised support absorption, saving paint accordingly.

How to use

- 1) Prepare and clean substrate.
- 2) Water to add 0.600 litres / sac 1.5 kg.
- 3) Manual application.
- 4) Mixture workable for 6 hours.
- 5) Clean tools with water.

Recommendations

Do not use at low temperatures.
Prime very absorbent substrates.
Isolate and protect metallic parts with an anti-corrosion primer.
Do not apply on substrates subject to constant humidity.
Stir until an even paste is achieved.
Apply with stainless steel trowel or scraper.
Do not apply on humid substrates.

Precautionary statements

P102 Keep out of reach of children.
P260 Do not breathe dust.
P262 Do not get in eyes, on skin, or on clothing.
P280 Wear protective gloves/eye protection/face protection.

Features

Fine matt white finish.
Mix life: Approx. 6 hours.
Drying time: 2 – 4 h. x mm.
Shelf life 12 months if sheltered.

Yield

It varies depending on the type of application.
Theoretical consumption +/- 1 kg / m² per mm thickness.

Presentation and delivery

1.5 kg inner polypropylene bag in plastic bucket and pallet with 160 buckets (240 kg).
4,5 kg (3 x 1,5 kg) inner polypropylene bag in plastic bucket and pallet with 105 buckets (472,5 kg).