



MORTELAN Yeso

- Repair of walls and ceilings.
- Filling of holes in interiors.

Description and uses of the product

Plaster preparation, fine finish and easy application, valid for all types of repairs in interior wall spaces, quickly and economically.

Suitable for fastening, anchoring and recessing of: boxes, electrical and plumbing equipment.

Valid for repairs of plasterboard plates.

How to use

- 1) Prepare and clean substrate.
- 2) Water to add 0.500 litres / 1 kg bag
- 3) Manual application.
- 4) Mixture workable for 8 minutes.
- 5) Clean tools with water.

Recommendations:

Application temperature + 5°C to + 30°C

Wet the support before applying the product.

The supports must be bonded well, should this not be the case apply a primer.

Apply the mixture with a plastering trowel when laying.

Do not apply on supports with permanent humidity.

Features

Fine matt white finish.

Setting time: 20 min.

Resistance against a flexural strength more than 20 kg/cm².

Shelf life 12 months if sheltered.

Yield

It varies according to the type of application.

Theoretical consumption 1.1 kg / m² per mm of thickness.

Presentation and delivery

1 kg inner polypropylene bag in plastic bucket and pallet with 160 buckets (160 kg).

3 kg (3 x 1 kg) inner polypropylene bag in plastic bucket and pallet with 105 buckets (315 kg).



MORTELAN
SOLUCIONES PARA TU CASA

MORTELAN Yeso

Precautionary statements

P102 Keep out of reach of children.

P260 Do not breathe dust.

P262 Do not get in eyes, on skin, or on clothing.

P280 Wear protective gloves/eye protection/face protection.