

Repair of walls and ceilings.

Filling of holes in interiors.



## Description and uses of the product

Plaster preparation, fine finish and easy application, valid for all types of repairs in interior wall spaces, quickly and economically.

Suitable for fastening, anchoring and recessing of: boxes, electrical and plumbing equipment.

Valid for repairs of plasterboard plates.

*'Valid for repairs of plasterboard plates'*

## How to use

1. Prepare and clean substrate.
2. Water to add 0,500 litres / 1 kg bag
3. Manual application.
4. Mixture workable for 8 minutes.
5. Clean tools with water.

## Recommendations

Do not apply at temperatures below 5 °C.

Moisten the support before applying the product.

On highly absorbent or disintegrable supports, it is recommended the application of the consolidant of surfaces **GECOL Primer-TP** 1:2 diluted in water.

Apply with a trowel or trowel depending on the operation to be carried out.

Do not use on supports with permanent humidity.

## Features

Colour: white.

Rest time: 3 minutes.

Setting time: 20 minutes.

Storage: 12 months under normal conditions.

## Yield

It varies according to the type of application.

Theoretical consumption : 1,10 kg/m<sup>2</sup> per mm of thickness.

## Presentation and delivery

**1 kg bucket:** 1 kg polypropylene bag in a plastic mixing bucket.

**3 kg bucket:** 3 polypropylene bags of 1 kg (3 x 1 kg) in a mixing plastic bucket.

## Precautionary statements

**P102** Keep out of reach of children.  
**P260** Do not breathe dust.

**P262** Do not get in eyes, on skin, or on clothing.  
**P280** Wear protective gloves/eye protection/face protection.